Declaration of Performance



Norscot Joinery Limited Bower Workshops, Bower, Wick KW1 4TL



14

NORSCOT Timber Door, intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006 + A1:2010

Watertightness: NPD

Dangerous substances: None released under normal indoor use.

Resistance to wind load: NPD

Load-bearing capacity of safety devices: **Pass, 350N when fitted** (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m2K}(2)$

Radiation properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented, maintained and accredited to ISO 9001: 2008. Certificate No 518, BM TRADA Certification Notified test Body No. 012.

- (1) Report No. 310901 dated 19/09/2011 for restrictor Exova Warringtonapt Notified Test Body No. 0621.
- (2) Thermal Transmittance calculation approved by Exova Warringtonapt, Notified Test Body No 0621, Ref Report No WIL 331063-2 dated 02/12/2013

Storage, Handling, Safety and Installation, Operation, Maintenance and Care instructions as well as Reach Regulations are available on line at www.norscot.co.uk/windows-doors/CE-marking

Jason Fraser Name

Technical Director 2 December 2013, Bower Office

Position

Date and Place of Issue